

# ***SP-12 Spray Unit***

## *Primary uses:*

- *Moulding and trim*
- *Door jambs and cabinet components*
- *Wood flooring*



## Standard Features:

- Compatible with both waterborne and solvent based coatings
- Maximum part width: 12"
- Maximum part height: 3"
- Minimum part length: 36"
- Maximum line speed 150 fpm
- Must be used in a functional spray booth unless the machine is equipped with the optional exhaust system
- Fluid system with three spray guns, fluid filter, & fluid pump included
- Three adjustable gun arms
- 9'-0" long variable speed live roll conveyor
- Pneumatic gun trigger mechanism to automatically trigger guns on/off
- De-nib station mounted to infeed with choice of sanding head or nylon de-nib brush

## Optional Equipment/Features:

- Removable rollers to transfer parts across spray area (14" minimum part length)
- Stain wipe station mounted to outfeed with stain wipe brush
- Exhaust system with spray enclosure, exhaust fan, & exhaust filter system
- Conversion to pump system with individual gun regulators
- Conversion to photo eye gun trigger
- Addition of manual spray gun
- Machine sold without de-nib station or without pump & gun system

Solidly constructed for long term reliability and manufactured in the U.S., to assure fast response and prompt availability of replacement parts from local suppliers.